

Steel scope rings are usually shipped with an oily film to prevent rust. Make sure to use a degreasing agent to remove oil or grease from the inside of the scope rings before the scope is mounted.

**SWAROVSKI OPTIK Z3 Series - 1" (25.4 mm) tubes**

Model	Maximum range of adjustment @ 100 yards	Point of impact (click) per click @ 100 yards	Total no. of clicks (approx.)
3-9x36			
Elevation	57.6 in	.25 in	230 clicks
Windage	57.6 in	.25 in	230 clicks
3-10x42			
Elevation	50.4 in	.25 in	202 clicks
Windage	50.4 in	.25 in	202 clicks
4-12x50			
Elevation	43.2 in	.25 in	173 clicks
Windage	43.2 in	.25 in	173 clicks

**SWAROVSKI OPTIK Z5 Series - 1" (25.4 mm) tubes**

Model	Maximum range of adjustment @ 100 yards	Point of impact (click) per click @ 100 yards	Total no. of clicks (approx.)
3.5-18x44			
Elevation	57.6 in	.25 in	230 clicks
Windage	36 in	.25 in	144 clicks
5-25x52			
Elevation	43.2 in	.25 in	173 clicks
Windage	25.2 in	.25 in	101 clicks

\* The BT models in the Z3 4-12x50, Z5 3.5-18x44 and Z5 5-25x52 will have the same total number of clicks, with the coupling off (as when making initial elevation adjustments when sighting in).

**Proper Mounting of Scope to Insure Ultimate Accuracy & Reliability**



SWAROVSKI OPTIK

SWAROVSKI OPTIK NORTH AMERICA LTD  
 2 Slater Road • Cranston RI 02920  
 Tel. 800-426-3089 • Fax 877-287-8517  
 info@swarovskioptik.us  
**WWW.SWAROVSKIOPTIK.COM**

SWAROVSKI OPTIK